



**DEPARTMENT OF HEALTH**  
 STATE HEALTH OFFICE  
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS  
 SEPTIC TANK MANUFACTURERS  
 run date: 7/19/2011

**Florida Septic, Inc.**

ACTIVE

Alachua

Post Office Box 545  
 Hawthorne, FL 32640

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL	APPROVAL USE	DATE
				WIDTH	LENGTH		GALLONS (Pump Tanks)		
01-011-02D-C4	C4	4.00	52.30			750			5/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-02S-C4	C4	4.00	52.30			750			5/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-03D-C4	C4	6.00	55.25			1050			10/31/2001
REMARKS:									
01-011-03S-C4	C4	6.00	55.25			1050			10/31/2001
REMARKS:									
01-011-04D-C3	C3	2.50	43.50			900			1/31/2001
REMARKS:									
01-011-06D-C4	C4	6.00	53.00			750			10/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-06S-C4	C4	6.00	53.00			750			10/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-07S-C3	C3	2.50	51.75			1050	Standa		6/11/2002
REMARKS: Can be used to house Bio-Microbics MicroFast 0.5 ATU when used with 350 gallon min. settling tank									
01-011-09D-C3	C3	2.50	50.00			1050			1/31/2001
REMARKS: Houses Bionest BNC-400 ATU									
01-011-09S-C3	C3	2.50	50.00	62.3	101.3	1050	1,270		2/29/2008
REMARKS:									
01-011-10D-C4	C4	4.00	55.00			1050			5/31/2001
REMARKS:									
01-011-10S-C4	C4	4.00	55.00			1050			5/31/2001
REMARKS:									
01-011-11D-C4	C4		44.00			1050	1,348		3/17/2003
REMARKS: Houses Bionest BNC-400 ATU. Wall thickness can be either 4" or 6". AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-11S-C4	C4		44.00			1050	1,348		3/17/2003
REMARKS: Wall thickness can be either 4" or 6". AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-12D-C3	C3	2.50	49.00			1200			12/14/2001
REMARKS:									
01-011-12S-C3	C3	2.50	49.00			1200			12/14/2001
REMARKS:									



**DEPARTMENT OF HEALTH**  
 STATE HEALTH OFFICE  
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS  
 SEPTIC TANK MANUFACTURERS  
 run date: 7/19/2011

**Florida Septic, Inc.**

ACTIVE

Alachua

Post Office Box 545  
 Hawthorne, FL 32640

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)	APPROVAL USE	DATE
				WIDTH	LENGTH				
01-011-13D-C4	C4		52.00			1250	1,564		3/17/2003
REMARKS: Houses Bionest BNC-500 ATU. Wall thickness can be either 4" or 6". AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-13S-C4	C4		52.00			1250	1,564		3/17/2003
REMARKS: Wall thickness can be either 4" or 6". AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-16D-C3	C3	3.00	57.40			1350			5/31/2001
REMARKS:									
01-011-16S-C3	C3	3.00	57.40			1350			5/31/2001
REMARKS:									
01-011-19D-C4	C4	4.00	46.00			1350			7/30/2001
REMARKS:									
01-011-19S-C4	C4	4.00	46.00			1350			7/30/2001
REMARKS:									
01-011-20D-C3	C3	3.00	63.00			1500			5/31/2001
REMARKS: Houses Bionest BNC-600 ATU.									
01-011-20S-C3	C3	3.00	63.00			1500			5/31/2001
REMARKS:									
01-011-22D-C4	C4	4.00	41.50	75.2	151	1530	2,063		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-22S-C4	C4	4.00	41.50	75.2	151	1530	2,063		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-23D-C4	C4	4.00	53.00			1500			7/30/2001
REMARKS: Houses Bionest BNC-600 ATU									
01-011-23S-C4	C4	4.00	53.00			1500			7/30/2001
REMARKS:									
01-011-24D-C3	C3	3.00	44.00			1650			7/30/2001
REMARKS:									
01-011-24S-C3	C3	3.00	44.00			1650			7/30/2001
REMARKS:									
01-011-27D-C4	C4	6.00	53.00			1500			10/31/2001
REMARKS: Houses Bionest BNC-600 ATU. AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-27S-C4	C4	6.00	53.00			1500			10/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									



**DEPARTMENT OF HEALTH**  
 STATE HEALTH OFFICE  
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS  
 SEPTIC TANK MANUFACTURERS  
 run date: 7/19/2011

**Florida Septic, Inc.**

ACTIVE

Alachua

Post Office Box 545  
 Hawthorne, FL 32640

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL	APPROVAL USE DATE
				WIDTH	LENGTH		GALLONS (Pump Tanks)	
01-011-28D-C4	C4	6.00	41.50	79.2	155	1530	2,062	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-28S-C4	C4	6.00	41.50	79.2	155	1530	2,062	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-29D-C4	C4	4.00	44.00			1650		7/30/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-29S-C4	C4	4.00	44.00			1650		7/30/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-30D-C4	C4	6.00	44.00			1650		5/29/2002
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-30S-C4	C4	6.00	44.00			1650		5/29/2002
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-35D-C4	C4	4.00	50.50	76.3	152.8	1890	2,449	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-35S-C4	C4	4.00	50.50	76.3	152.8	1890	2,449	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-36D-C4	C4	6.00	50.50	80.3	156.8	1890	2,449	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-36S-C4	C4	6.00	50.50	80.3	156.8	1890	2,449	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-37D-C3	C3	3.00	53.00			2000		7/30/2001
REMARKS: Houses Bionest BNC-750 ATU								
01-011-37S-C3	C3	3.00	53.00			2000		7/30/2001
REMARKS:								
01-011-38D-C4	C4	4.00	53.00			2000		7/30/2001
REMARKS: Houses Bionest BNC-750 ATU								
01-011-38S-C4	C4	4.00	53.00			2000		7/30/2001
REMARKS:								
01-011-39D-C4	C4	6.00	53.00			2000		5/29/2002
REMARKS: Houses Bionest BNC-750 ATU. AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-39S-C4	C4	6.00	53.00			2000		5/29/2002
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-40D-C3	C3	3.00	60.00			2300		7/30/2001
REMARKS:								



**DEPARTMENT OF HEALTH**  
 STATE HEALTH OFFICE  
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS  
 SEPTIC TANK MANUFACTURERS  
 run date: 7/19/2011

**Florida Septic, Inc.**

Post Office Box 545  
 Hawthorne, FL 32640

ACTIVE

Alachua

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL	APPROVAL USE	DATE
				WIDTH	LENGTH		GALLONS (Pump Tanks)		
01-011-40S-C3	C3	3.00	60.00			2300			7/30/2001
REMARKS:									
01-011-41D-C4	C4	4.00	60.00			2300			7/30/2001
REMARKS:									
01-011-41S-C4	C4	4.00	60.00			2300			7/30/2001
REMARKS:									
01-011-42D-C4	C4	4.00	63.50	78	154.5	2445	3,021		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-42S-C4	C4	4.00	63.50	78	154.5	2445	3,021		4/9/2008
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.									
01-011-43D-C4	C4	4.00	66.00			2500			7/30/2001
REMARKS: Houses Bionest BNC-1000 ATU									
01-011-43S-C4	C4	4.00	66.00			2500			7/30/2001
REMARKS:									
01-011-44D-C4	C4	4.00	57.50	77.2	153.5	2180	2,752		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-44S-C4	C4	4.00	57.50	77.2	153.5	2180	2,752		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-45D-C4	C4	6.00	57.50	81.2	157.5	2180	2,752		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-45S-C4	C4	6.00	57.50	81.2	157.5	2180	2,752		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-46D-C4	C4	6.00	66.25			2500			5/29/2002
REMARKS:									
01-011-46S-C4	C4	6.00	66.25			2500			5/29/2002
REMARKS:									
01-011-47D-C4	C4	6.00	63.50	82	158.5	2445	3,023		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-47S-C4	C4	6.00	63.50	82	158.5	2445	3,023		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-49D-C4	C4	6.00	66.00			2500			5/29/2002
REMARKS: Houses Bionest BNC-1000 ATU. AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-49S-C4	C4	6.00	66.00			2500			5/29/2002
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									



**DEPARTMENT OF HEALTH**  
 STATE HEALTH OFFICE  
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS  
 SEPTIC TANK MANUFACTURERS  
 run date: 7/19/2011

**Florida Septic, Inc.**

ACTIVE

Alachua

Post Office Box 545  
 Hawthorne, FL 32640

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL	APPROVAL USE DATE
				WIDTH	LENGTH		GALLONS (Pump Tanks)	
01-011-51S-C4	C4	4.00	43.00	99.5	187.6	2825	3,733	4/9/2008
REMARKS: 6" inlet and 2-4" outlets.								
01-011-52D-C4	C4	4.00	42.50			2800		8/14/2001
REMARKS:								
01-011-52S-C4	C4	4.00	42.50			2800		8/14/2001
REMARKS:								
01-011-53D-C4	C4	6.00	42.50			2800		10/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-53S-C4	C4	6.00	42.50			2800		10/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-54D-C4	C4	4.00	43.00	99.5	187.6	2825	3,733	4/9/2008
REMARKS: 6" inlet and outlet.								
01-011-54S-C4	C4	4.00	43.00	99.5	187.6	2825	3,733	4/9/2008
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.								
01-011-55D-C4	C4	6.00	43.00	103.5	191.6	2825	3,733	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-55S-C4	C4	6.00	43.00	103.5	191.6	2825	3,733	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-56D-C4	C4	4.00	45.25			3000		8/14/2001
REMARKS:								
01-011-56S-C4	C4	4.00	45.25			3000		8/14/2001
REMARKS:								
01-011-57D-C4	C4	6.00	45.50			3000		10/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-57S-C4	C4	6.00	45.50			3000		10/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-60D-C4	C4	6.00	60.00			2300		5/29/2002
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-60S-C4	C4	6.00	60.00			2300		5/29/2002
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-62D-C4	C4	4.00	47.00	99.75	188	3100	4,018	4/9/2008
REMARKS: 6" inlet and outlet.								
01-011-62S-C4	C4	4.00	47.00	99.75	188	3100	4,018	4/9/2008
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.								



**DEPARTMENT OF HEALTH**  
 STATE HEALTH OFFICE  
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS  
 SEPTIC TANK MANUFACTURERS  
 run date: 7/19/2011

**Florida Septic, Inc.**

ACTIVE

Alachua

Post Office Box 545  
 Hawthorne, FL 32640

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL	APPROVAL DATE
				WIDTH	LENGTH		GALLONS (Pump Tanks) USE	
01-011-63D-C4	C4	6.00	47.00	103.7	192	3100	4,017	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-63S-C4	C4	6.00	47.00	103.7	192	3100	4,017	4/9/2008
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.								
01-011-64D-C3	C3	4.00	50.00			3300		8/14/2001
REMARKS: Houses Bionest BNC-1250 ATU								
01-011-64S-C3	C3	4.00	50.00			3300		8/14/2001
REMARKS:								
01-011-64S-C4	C4	4.00	49.50	99.75	188	3300	4,023	8/12/2008
REMARKS:								
01-011-65D-C4	C4	6.00	49.50			3300		10/31/2001
REMARKS: Houses Bionest BNC-1250 ATU. AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-65S-C4	C4	6.00	49.50			3300		10/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-66D-C3	C3	4.00	63.25	100.1	188.4	3500	4,461	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-66S-C3	C3	4.00	63.25	100.1	188.4	3500	4,461	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-67D-C4	C4	6.00	53.25	104.1	192.4	3500	4,461	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-67S-C4	C4	6.00	53.25	104.1	192.4	3500	4,461	4/9/2008
REMARKS: 6" inlet and outlet								
01-011-68D-C3	C3	4.00	54.00			3700		8/14/2001
REMARKS: Houses Bionest BNC-1500 ATU								
01-011-68S-C3	C3	4.00	54.00			3700		8/14/2001
REMARKS:								
01-011-69D-C4	C4	6.00	55.00			3700		5/29/2002
REMARKS: Houses Bionest BNC-1500 ATU. AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-69S-C4	C4	6.00	55.00			3700		5/29/2002
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"								
01-011-70D-C3	C3	4.00	62.00	101.1	189.5	4150	5,109	4/9/2008
REMARKS: 6" inlet and outlet.								
01-011-70S-C3	C3	4.00	62.00	101.1	189.5	4150	5,109	4/9/2008
REMARKS: 6" inlet and outlet								



**DEPARTMENT OF HEALTH**  
 STATE HEALTH OFFICE  
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS  
 SEPTIC TANK MANUFACTURERS  
 run date: 7/19/2011

**Florida Septic, Inc.**

ACTIVE

Alachua

Post Office Box 545  
 Hawthorne, FL 32640

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL	APPROVAL USE	DATE
				WIDTH	LENGTH		GALLONS (Pump Tanks)		
01-011-71D-C4	C4	6.00	62.00	105.1	193.4	4150	5,107		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-71S-C4	C4	6.00	62.00	105.1	193.4	4150	5,107		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-72D-C3	C3	4.00	64.50			4300			8/14/2001
REMARKS:									
01-011-72S-C3	C3	4.00	64.50			4300			8/14/2001
REMARKS:									
01-011-73D-C4	C4	6.00	64.50			4300			5/29/2002
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-73S-C4	C4	6.00	64.50			4300			5/29/2002
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-74D-C4	C4	6.00	72.80	109	194.7	4900	5,910		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-74S-C4	C4	6.00	72.80	109	194.7	4900	5,910		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-76D-C3	C3	4.00	72.00			5000			8/14/2001
REMARKS:									
01-011-76S-C3	C3	4.00	72.00			5000			8/14/2001
REMARKS:									
01-011-77D-C4	C4	6.00	72.00			5000			5/29/2002
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-77S-C4	C4	6.00	72.00			5000			5/29/2002
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-78D-C3	C3	4.00	72.80	102	190.75	4900	5,916		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-78S-C3	C3	4.00	72.80	102	190.75	4900	4,916		4/9/2008
REMARKS: 6" inlet and outlet									
01-011-90D-C4	C4	4.00	43.00			1250			7/30/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-90S-C4	C4	4.00	43.00			1250			7/30/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-91D-C4	C4	6.00	43.00			1250			10/31/2001
REMARKS:									



**DEPARTMENT OF HEALTH**  
 STATE HEALTH OFFICE  
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS  
 SEPTIC TANK MANUFACTURERS  
 run date: 7/19/2011

**Florida Septic, Inc.**

ACTIVE

Alachua

Post Office Box 545  
 Hawthorne, FL 32640

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)	APPROVAL USE	APPROVAL DATE
				WIDTH	LENGTH				
01-011-91S-C4	C4	6.00	43.00			1250			10/31/2001
REMARKS:									
01-011-92D-C4	C4	6.00	46.00			1350			10/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-92S-C4	C4	6.00	46.00			1350			10/31/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-93S-C4	C4	4.00	42.00			300			12/14/2001
REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48"									
01-011-94-C4	C4	4.00	34.75			300	358		6/8/2005
REMARKS: Siphon tank.									
01-011-96S-C4	C4	3.00	42.00			300			1/31/2001
REMARKS:									
01-011-97S-C4	C4	3.00	42.00			525			1/31/2001
REMARKS:									
01-011-AK10-C3	C3	3.00	56.50	62	119	1342	1,583		8/12/2008
REMARKS: Houses AquaKlear AK1000C 1000 gallon per day ATU									
01-011-AK5-C4	C4	3.00	49.50			640	773	ATU ta	12/14/2005
REMARKS: Used to house AquaKlear 500 gallon per day ATU.									
01-011-AK5B-C3	C3	3.00	50.50	81.38	139.5	1875		ATU	8/27/2007
REMARKS: Houses AquaKlear AK5B3 500 gpd ATU unit and dosing pump.									
01-011-AK8-C3	C3	3.00	57.50			1020	1,193	ATU ta	12/14/2005
REMARKS: Used to house AquaKlear 800 gallon per day ATU.									
01-011-BM1-C3	C3	3.00	45.00			1100	1,479	ATU ta	10/31/2003
REMARKS: Used to house Bio-Microbics FAST 0.5FS ATU									
01-011-BM2-C4	C4	4.00	53.00			1500	1,919	ATU ta	10/31/2003
REMARKS: Used to house Bio-Microbics FAST 0.75FS and 0.9FS ATU									
01-011-BM3-C4	C4	4.00	57.00			2150	2,752	ATU ta	10/31/2003
REMARKS: Used to house Bio-Microbics FAST 1.5FS ATU									
01-011-BM4-C3	C3	3.00	43.00			1600	2,433	ATU ta	10/31/2003
REMARKS: Used to house Bio-Microbics FAST 0.5F, 0.75F, and 0.9F ATU									
01-011-BM5-C3	C3	4.00	66.00			4500	5,909	ATU ta	10/31/2003
REMARKS: Used to house Bio-Microbics FAST 3.0F and 3.0FS ATU									
01-011-BM6-C3	C3	4.00	65.00			4400	5,913	ATU ta	2/17/2004
REMARKS: Used to house Bio-Microbics FAST 4.5F ATU									



**DEPARTMENT OF HEALTH**  
 STATE HEALTH OFFICE  
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS  
 SEPTIC TANK MANUFACTURERS  
 run date: 7/19/2011

**Florida Septic, Inc.**

ACTIVE

Alachua

Post Office Box 545  
 Hawthorne, FL 32640

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL	USE	APPROVAL DATE
				WIDTH	LENGTH		GALLONS (Pump Tanks)		
01-011-BM7-C4	C4	4.00	63.00	78	154.5	2400	3,021	ATU ta	9/13/2007
REMARKS: Used to house Bio-Microbics FAST 1.5F or S ATU. Inlet and/or outlet can be 4" or 6".									
01-011-CS1-C4	C4	3.00	55.00	84	155		2,232		5/12/2010
REMARKS: Used to house the Clearstream model 600NC3T treatment unit									
01-011-FT1-C3	C3	3.00	30.50			1150	1,505	Filter M	7/29/2005
REMARKS: Filter media tank w/65 sq ft surface area									
01-011-FT2-C4	C4	4.00	29.50	98.25	186.5	1950	2,648	Filter M	1/3/2007
REMARKS: Filter media tank w/112 sq ft surface area									
01-011-FT3-C3	C3	4.00	30.50	0	0	1150	1,505	filter m	4/30/2007
REMARKS: Filter media tank w/65 sq ft surface area									